



Rock Mass Response to Longwall Advance Under Thick Sandstone Roof Conditions: A Review of the Literature

Tigist Teixeira^{1*}, Lars Natarajan², Tigist Ndlovu³

¹Department of Engineering, Altai Graduate Institute of Engineering, Portugal

²Department of Engineering, Ural Academy of Engineering, Greece

³Department of Engineering, Danube Center for Engineering, Malaysia

Article Info

Volume 1, Issue 1, 2026

doi: [10.62715/ijme.2026.v1.i1.pp1-7](https://doi.org/10.62715/ijme.2026.v1.i1.pp1-7)

Received: 25 December 2025

Accepted: 10 March 2026

Published: 26 April 2026

Abstract

Longwall mining depends on the roof caving in an orderly way behind the powered supports. Where a thick, strong sandstone unit lies close above the seam, that assumption is strained: the unit bridges the goaf, hangs up behind the face and then breaks at intervals, and the face experiences periodic weighting, high abutment stress and, in the worst cases, windblast or coal bursts. This article is a narrative review of the published literature on how the rock mass responds to longwall advance under such roofs. It covers the zoning of the disturbed overburden, the beam, voussoir and key strata models used to explain first and periodic weighting, the interaction between shields and strata, the redistribution of stress into abutments and gate road pillars, dynamic hazards, surface subsidence and effects on groundwater, and the measures used to induce caving, chiefly hydraulic fracturing and long-hole blasting. Numerical modelling and monitoring methods are assessed for what they can and cannot establish. The review finds broad agreement on mechanisms and much less on prediction, because the governing variables, especially the thickness, position and jointing of the sandstone, differ from panel to panel and are seldom reported in comparable form.

Keywords: Longwall mining, Massive sandstone roof, Periodic weighting, Key strata, Shield support, Hard roof control

© 2026 Tigist Teixeira et al. This is an open access article under the CC BY license (<https://creativecommons.org/licenses/by/4.0/>), which permits unrestricted use, distribution, and reproduction in any medium, provided you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons license, and indicate if changes were made.

1. Introduction

A longwall face removes a panel of coal several hundred metres wide in a single pass and lets the roof fall behind it. The method works because most Coal Measures roofs are weak and thinly bedded: mudstones, siltstones and laminated sandstones break up soon after the shields advance, bulk as they fall and fill the void, so that the overlying beds are cushioned within a short distance of the face. The design of the supports, the gate road pillars and the panel itself all rest on this behaviour (Peng and Chiang, 1984; Peng, 2020).

A thick sandstone unit near the seam changes the picture. Channel sandstones and sheet sandstones tens of metres thick, with widely spaced bedding and joints, are common in coalfields in Australia, China,

* Corresponding author: Tigist Teixeira, Department of Engineering, Altai Graduate Institute of Engineering, Portugal. E-mail: tigist.teixeira@altai.edu


© 2026 Tigist Teixeira et al. This is an open access article distributed under the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

India, South Africa, Central Europe and the western United States. Such a unit does not fall with the immediate roof. It spans the goaf as a plate, sheds its weight onto the face and the panel edges, and fails only when the span has grown large enough. The consequences are familiar to operators: heavy first weighting, periodic weighting that can close the shields, overhang at the tailgate corner, bursts in the face or the gate roads, and sudden falls of large areas of goaf roof (Galvin, 2016).

This article reviews what the published literature says about that response. It is a narrative review drawn from standard texts, widely cited journal papers and conference proceedings in ground control; it does not claim an exhaustive search and it reports no new measurements. The aim is to set out where the field agrees, where it does not, and what would be needed to move from explanation to dependable prediction.

2. Zoning of the Disturbed Overburden

Most accounts divide the strata above a longwall goaf into zones, and Figure 1 shows the arrangement when a thick sandstone is present. Immediately above the seam is the caved zone, where rock has fallen, rotated and bulked. Above it lies the fractured zone, in which beds have broken into blocks that remain in contact and bed separations open and close as the face passes. Higher still the strata sag without losing continuity, and at the surface a subsidence trough forms. Peng and Chiang (1984) describe four zones in these terms, and the Chinese literature a comparable set of three (Bai et al., 1995).



The heights of the caved and fractured zones are usually expressed as multiples of the extracted height, and the multiples depend on lithology. Compilations of field observations show that strong, hard overburden produces a higher fractured zone than weak overburden for the same extraction, because stiff beds break into large blocks that do not reseal (Bai et al., 1995; Palchik, 2003). The simple rule that caving stops once the bulked debris fills the void was examined by Salamon (1990), who showed how the result depends on the bulking factor assumed. That factor is hard to measure and is lower for blocky sandstone debris than for shale.

Zoning is a description and not a mechanism. It says little about when a particular bed will break, and under a thick sandstone the boundaries between zones are not fixed in time: a unit that sits in the continuous deformation zone while it bridges becomes part of the fractured zone the moment it fails. For that reason most work on hard roofs has turned to models of the individual strong bed.

3. Mechanical Models of the Strong Bed

Four families of model recur in the literature, and Table 1 summarises them. They are best read as successive refinements, each keeping the insight of the one before and correcting one of its omissions.

Table 1: Principal models used to explain the behaviour of a thick, strong roof bed above a longwall face			
Model	Central idea	What it explains	Main limitation
Elastic beam or plate (Obert and Duvall, 1967)	Bed spans the goaf as a clamped beam, then a cantilever	First weighting longer than periodic weighting	Ignores jointing and arching after cracking
Voussoir beam (Diederichs and Kaiser, 1999)	Cracked bed carries load through a compressive arch	Stability of jointed beds; failure by buckling, crushing or slip	Derived for static excavations of fixed span
Key strata (Qian et al., 1996)	One or more stiff beds control the movement of all strata above them	Stepped subsidence, bed separation, long weighting intervals	Needs full stratigraphy and bed properties
Detached block (Peng and Chiang, 1984)	Supports carry a block of immediate roof up to the first parting	Required support density at the face	Main roof load transfer treated crudely
Ground response curve (Medhurst and Reed, 2005)	Roof convergence falls as support resistance rises	Effect of setting pressure and shield stiffness	Curve must be calibrated for each site
Distinct element simulation (Gao et al., 2014)	Strata represented as bonded blocks that can fracture	Caving sequence and block size without prior assumption	Calibration; usually two-dimensional

Classical beam theory treats the strong bed as an elastic beam clamped at both ends before the first break and as a cantilever afterwards. Because a clamped beam can span further than a cantilever of the same section before reaching its tensile strength, the theory accounts for the common observation that the first weighting interval is roughly twice the periodic interval or more (Obert and Duvall, 1967; Peng, 2020). It also shows why thickness matters so much: the limiting span grows with bed thickness, so a thick sandstone can hang over a wide area of goaf.

Real beds are cut by joints, and once a bed has cracked it does not lose all capacity. The voussoir analogue describes how a jointed beam carries load through a compression arch between its abutments and fails by snap-through buckling, by crushing at the hinges or by sliding on the abutment joints. The treatment by Diederichs and Kaiser (1999) is the usual reference, and Brady and Brown (2004) set it in the wider context of excavations in stratified rock. In the Chinese literature the same idea appears as the articulated or "masonry" beam of broken blocks behind the face, whose rotation and sliding govern the load delivered to the supports.

The key strata theory of Qian and colleagues extends the argument from one bed to the column. A key stratum is a stiff, thick bed that carries the softer beds above it; when it breaks, everything it carried moves with it. A sequence may contain several, with the highest governing surface movement (Qian et al., 1996). The theory explains bed separation beneath a bridging unit, stepped subsidence and the very long weighting intervals recorded under thick sandstones. On faces with large mining height the theory also implies that a sandstone which would be part of the main roof at ordinary heights can fall within the caved zone and behave as a cantilever instead of a hinged beam.

4. Shield and Strata Interaction

A recurring finding is that powered supports cannot hold up the main roof. Their function is to keep the immediate roof intact and in contact with the beds above, so that the strong bed breaks behind the shields

and not over the face. The detached block approach frames the design load as the weight of a block of roof separated up to the first parting, with an allowance for the main roof (Peng and Chiang, 1984). Under a thick sandstone with thin immediate roof that block is ill defined, and the load on the supports is set mostly by the rotation of the bridging bed, which the supports can influence only slightly.

The ground response approach makes the same point in a different way. Convergence at the face decreases as support resistance increases, steeply at first and then with diminishing return, and the practical questions are where a given shield sits on that curve and how quickly it gets there after being set (Medhurst and Reed, 2005). Trueman *et al.* (2009) developed a method of reading the leg pressure record of each shield cycle to classify behaviour, distinguishing cycles in which pressure levels off from those in which it climbs to yield. Their work, and the practice built on it, treats the leg pressure history as the most widely available measurement of roof behaviour on a modern face, and most weighting forecasts in use rest on it.

Setting pressure, the tip-to-face distance, face advance rate and stoppages all appear in the literature as influences on the severity of a weighting event. The evidence for advance rate is mostly observational: slow or halted faces tend to show more convergence, which fits time-dependent deformation of the immediate roof, but the effect is difficult to separate from the geological reasons why a face slowed in the first place (Galvin, 2016).

5. Abutment Stress and Gate Roads

Load that the goaf does not carry is transferred to the solid coal ahead of the face and to the pillars and barriers at the panel sides. The Analysis of Longwall Pillar Stability method estimates the side abutment load from a wedge of overburden defined by an abutment angle, a value back-analysed from United States case histories (Mark, 1990). In British practice the stress in the yielded coal at the panel edge is obtained from the stress balance analysis of Wilson (1983). Under massive strata the wedge can be larger than the default implies, because a bridging bed delays the reloading of the goaf, and several authors have warned against carrying the standard angle into strong-roof coalfields without local calibration (Galvin, 2016).

How quickly the goaf takes up load again is therefore central. Yavuz (2004) proposed a method for estimating the distance behind the face at which cover pressure is re-established, based on the compaction behaviour of caved material, and found that distance to depend on the extracted height and the strength of the caved rock. Roof quality in the gate roads is commonly rated with the Coal Mine Roof Rating of Molinda and Mark (1994), which scores bedding, strength and moisture sensitivity. A massive sandstone scores well on that scale, and this is one of the paradoxes of the subject: the roof that is easiest to support in development is the hardest to cave in extraction.

6. Dynamic Hazards

Three dynamic phenomena are associated with thick, strong roofs. The first is the sudden fall of a large area of standing goaf, which displaces air into the workings as a windblast. The second is the coal burst or bump, in which highly stressed coal in the face or rib is ejected, sometimes triggered by the fracture of the overlying bed. The third is severe periodic weighting, which is not violent in the same sense but can drive shields to full closure within a short period.

Seismic monitoring has been the main tool for studying these events. Australian work combining microseismic arrays with numerical models showed fracturing well ahead of the face and well above the caved zone, with shear on bedding as a leading mechanism, and changed the prevailing picture of caving as something that happens only behind the supports (Kelly *et al.*, 2002). These studies are site specific, and their value for other mines lies in the mechanisms they reveal more than in any transferable thresholds.

7. Surface Subsidence and Groundwater

Empirical subsidence prediction, in the tradition of the British handbook, relates maximum subsidence to the ratio of panel width to depth and to the extracted height (National Coal Board, 1975). The curves were

drawn from coalfields with weak, cyclothemic overburden. Where strong beds are present, subsidence over panels of subcritical width is smaller than those curves predict, because the beds span between the abutments, and it may then increase abruptly when an adjacent panel removes the support. This behaviour is documented for massive sandstones and conglomerates in New South Wales and for dolerite sills in South Africa ([Whittaker and Reddish, 1989](#); [Galvin, 2016](#)).

The same bridging has hydrological consequences. Connected fracturing above the goaf drains aquifers that lie within the fractured zone, while aquifers in the continuous deformation zone show head changes that often recover ([Booth, 1986](#)). Bed separations beneath a bridging sandstone can store water that is released into the workings when the bed fails. Since strong overburden tends to raise the top of the fractured zone, guidelines for mining under water bodies that were derived in weak strata need care when they are applied to hard-roof coalfields ([Bai et al., 1995](#); [Palchik, 2003](#)).

8. Inducing the Roof to Cave

If the sandstone will not break at a tolerable span, it can be weakened in advance. Two techniques dominate the literature. Hydraulic fracturing places fractures in the bed from boreholes drilled from the gate roads or the face, so that the bed is divided into thinner layers or shorter cantilevers. The work at an Australian colliery with a massive conglomerate roof, reported by [Jeffrey and Mills \(2000\)](#), is the best known account: fractures were used to bring down standing goaf on demand and so manage the windblast hazard. Directional variants, in which a notch controls where the fracture starts, have been described for burst-prone Chinese mines ([Fan et al., 2012](#)).

The second technique is long-hole blasting in the roof ahead of the face, used for many years in the Upper Silesian basin and in Indian hard-roof longwalls. [Konicek et al. \(2013\)](#) describe its application to destressing in deep Czech coal mines. Both techniques are judged in the literature mainly by the change in weighting interval, shield pressures and seismic energy release after treatment. Controlled comparisons are rare, since no two panels share the same geology, and reports of unsuccessful treatments are thinly represented in print. Design choices that avoid the problem are also discussed: orienting panels with respect to jointing, selecting face widths that ensure the bed fails, and specifying shields of high capacity and stiffness ([Peng, 2020](#)).

9. Numerical Modelling

Numerical models are now the usual means of bringing these elements together. Continuum codes with strain-softening and bedding-plane slip reproduced the fracturing ahead of the face inferred from seismicity ([Gale and Nemcik, 1998](#)). Distinct element models go further by letting blocks detach and rotate; the approach of [Gao et al. \(2014\)](#), in which the rock is tessellated into bonded triangular blocks, produces caving and periodic breakage without prescribing where fractures form.

The limits are well recognised. Rock mass properties are scaled from laboratory values by judgement, and the result is sensitive to that scaling. Most caving models are two-dimensional sections along the panel centreline, whereas a thick bed fails as a plate, with fractures that curve round the panel corners. Goaf reconsolidation is represented by an assumed hardening law. A model that matches the weighting interval at one site has shown that its assumptions are sufficient there, which is not the same as showing that it will predict the next.

10. Gaps and Directions for Further Work

Several gaps follow from the review. Published case descriptions seldom give the thickness of the strong unit, its height above the seam, its joint spacing and its strength in a consistent form, which makes comparison across coalfields difficult. A shared reporting convention for hard-roof panels would cost little and would let the empirical base grow. The lateral variability of channel sandstones is a related problem: exploration boreholes are too widely spaced to map changes in thickness that matter over a single panel, and geophysical methods that could fill the gaps deserve more systematic evaluation.

Shield leg pressures are recorded continuously on almost every modern face, yet their use for forecasting weighting remains largely site specific. Combining them with microseismic and surface

subsidence records in a common framework, and testing forecasts prospectively, would show how much warning the data can actually give. Finally, the effectiveness of preconditioning needs evidence that includes the cases where it did not work.

11. Conclusion

The literature gives a coherent account of why a thick sandstone roof makes longwall mining harder. The bed bridges, transfers load to the face and the abutments, and breaks at spans governed by its thickness, jointing and position in the sequence; supports control the immediate roof but not the bed itself; and the surface and groundwater response is delayed and then abrupt. What the literature does not yet offer is a general, tested method of predicting weighting intervals and intensities before a panel starts. Until it does, the sound course remains detailed characterisation of the strong unit, conservative choice of support and panel geometry, continuous monitoring, and readiness to precondition the roof.

Conflict of interest

To be declared by the author(s) before publication.

Funding

To be declared by the author(s) before publication.

References

- Bai, M., Kendorski, F.S. and Van Roosendaal, D.J. (1995). [Chinese and North American high-extraction underground coal mining strata behavior and water protection experience and guidelines](#). *Proceedings of the 14th International Conference on Ground Control in Mining*, West Virginia University, Morgantown, 209-217.
- Booth, C.J. (1986). [Strata-movement concepts and the hydrogeological impact of underground coal mining](#). *Ground Water*, 24(4): 507-515.
- Brady, B.H.G. and Brown, E.T. (2004). [Rock Mechanics for Underground Mining](#), 3rd edition. Kluwer Academic Publishers, Dordrecht.
- Diederichs, M.S. and Kaiser, P.K. (1999). [Stability of large excavations in laminated hard rock masses: The voussoir analogue revisited](#). *International Journal of Rock Mechanics and Mining Sciences*, 36(1): 97-117. [https://doi.org/10.1016/S0148-9062\(98\)00180-6](https://doi.org/10.1016/S0148-9062(98)00180-6)
- Fan, J., Dou, L., He, H., Du, T., Zhang, S., Gui, B. and Sun, X. (2012). [Directional hydraulic fracturing to control hard-roof rockburst in coal mines](#). *International Journal of Mining Science and Technology*, 22(2): 177-181.
- Gale, W.J. and Nemcik, J.A. (1998). [Prediction of strata caving characteristics and its impact on longwall operation](#). *Proceedings of the 1998 Coal Operators' Conference*, University of Wollongong, Wollongong.
- Galvin, J.M. (2016). [Ground Engineering: Principles and Practices for Underground Coal Mining](#). Springer, Cham. <https://doi.org/10.1007/978-3-319-25005-2>
- Gao, F., Stead, D. and Coggan, J. (2014). [Evaluation of coal longwall caving characteristics using an innovative UDEC Trigon approach](#). *Computers and Geotechnics*, 55: 448-460. <https://doi.org/10.1016/j.compgeo.2013.09.020>
- Jeffrey, R.G. and Mills, K.W. (2000). [Hydraulic fracturing applied to inducing longwall coal mine goaf falls](#). *Pacific Rocks 2000: Proceedings of the 4th North American Rock Mechanics Symposium*, Balkema, Rotterdam, 423-430.
- Kelly, M., Luo, X. and Craig, S. (2002). [Integrating tools for longwall geomechanics assessment](#). *International Journal of Rock Mechanics and Mining Sciences*, 39(5): 661-676.
- Konicek, P., Soucek, K., Stas, L. and Singh, R. (2013). [Long-hole destress blasting for rockburst control during deep underground coal mining](#). *International Journal of Rock Mechanics and Mining Sciences*, 61:

141-153.

Mark, C. (1990). *Pillar Design Methods for Longwall Mining*. Information Circular 9247, United States Bureau of Mines, Pittsburgh.

Medhurst, T.P. and Reed, K. (2005). *Ground response curves for longwall support assessment. Mining Technology (Transactions of the Institutions of Mining and Metallurgy: Section A)*, 114(2): 81-88.

Molinda, G.M. and Mark, C. (1994). *Coal Mine Roof Rating (CMRR): A Practical Rock Mass Classification for Coal Mines*. Information Circular 9387, United States Bureau of Mines, Pittsburgh.

National Coal Board (1975). *Subsidence Engineers' Handbook, 2nd edition*. National Coal Board Mining Department, London.

Obert, L. and Duvall, W.I. (1967). *Rock Mechanics and the Design of Structures in Rock*. John Wiley & Sons, New York.

Palchik, V. (2003). *Formation of fractured zones in overburden due to longwall mining. Environmental Geology*, 44(1): 28-38. <https://doi.org/10.1007/s00254-002-0732-7>

Peng, S.S. (2020). *Longwall Mining, 3rd edition*. CRC Press, London.

Peng, S.S. and Chiang, H.S. (1984). *Longwall Mining*. John Wiley & Sons, New York.

Qian, M.G., Miao, X.X. and Xu, J.L. (1996). *Theoretical study of key stratum in ground control. Journal of China Coal Society*, 21(3): 225-230.

Salamon, M.D.G. (1990). *Mechanism of caving in longwall coal mining. Rock Mechanics Contributions and Challenges: Proceedings of the 31st U.S. Symposium on Rock Mechanics*, Balkema, Rotterdam, 161-168.

Trueman, R., Lyman, G. and Cocker, A. (2009). *Longwall roof control through a fundamental understanding of shield-strata interaction. International Journal of Rock Mechanics and Mining Sciences*, 46(2): 371-380.

Whittaker, B.N. and Reddish, D.J. (1989). *Subsidence: Occurrence, Prediction and Control*. Elsevier, Amsterdam.

Wilson, A.H. (1983). *The stability of underground workings in the soft rocks of the Coal Measures. International Journal of Mining Engineering*, 1: 91-187.

Yavuz, H. (2004). *An estimation method for cover pressure re-establishment distance and pressure distribution in the goaf of longwall coal mines. International Journal of Rock Mechanics and Mining Sciences*, 41(2): 193-205. [https://doi.org/10.1016/S1365-1609\(03\)00082-0](https://doi.org/10.1016/S1365-1609(03)00082-0)